

PROCESS INDICATOR - PROGRAMMABLE



Model Function	PI 4955	PI 955	PI 755	PI 455
Size	(48 x 96 x 74) mm, Refer Size (4) table	(96 x 96 x 74) mm, Refer Size (1) table	(72 x 72 x 74) mm, Refer Size (2) table	(48 x 48 x 92) mm, Refer Size (3) table
LED Display	4 Digit, 0.5" Height			4 Digit, 0.39" Height
Multiple Input Sensor	Analog Input : A) Current : 1) 0 - 20 ma , 2) 4 - 20 ma B) Voltage : 1) 0 - 05 VDC, 2) 0 - 10 VDC, 3) 0 - 56 mVDC			
Display Range	- 1999 to 9999 : Scalable, in Forward / Reverse direction with programmable Bias - offset value.			
Resolution	0.001 / 00.01 / 000.1 / 0001 : Programmable.			
Accuracy	+/- 0.25 % of full scale or +/- 1 digit, whichever is greater.			
Sensor Supply	24 VDC / 30 ma output source (Inbuilt).			
Power Supply	90 to 250 VAC/DC @ 50/60 Hz.(24 VAC/DC provided on request)			
General Features	Setting by key pad , Mounting : Panel mounting type.			
Application	It is use to display following parameters, corresponds to the linear current / voltage input. RPM, MPM, AMP, HZ, % RH, °C, °F, KG/CM ² , mBAR, BAR, KG, RATE etc.			

OVER ALL MOUNTING DIMENSIONS (in mm)

SIZE \ DIM	DIM					
	A	B	C	D	E	F
SIZE - (1)	96	96	74	10	92	92
SIZE - (2)	72	72	74	10	69	69
SIZE - (3)	48	48	92	4	46	46